

# IP-900

## High Performance H.264 AVC Encoder

### Fujitsu Advanced MPEG-4 AVC Technology


Compact HD encoder for real-time HD/SD content delivery – Ideal for Enterprise, Government and Broadcasters

- ▶ High Performance H.264 encoded content over IP networks at low data rates
- ▶ Dual encoders provide two independent HD streams or independent HD/SD streams for Simulcast
- ▶ Rugged, lightweight 1RU half-rack width design
- ▶ Low power for mobile and transportable applications
- ▶ Region-of-Interest Processing – Provides Best Picture Fidelity
- ▶ Less than 400ms encode-decode latency
- ▶ Data Stream Protection with Advanced FEC/ARQ
- ▶ Auto-sensing 10/100/1000 Ethernet Output



**FUJITSU**

THE POSSIBILITIES ARE INFINITE



# IP-900

## High Performance H.264 AVC Encoder

The Fujitsu IP-900 HD/SD encoder utilizes advanced H.264 encoding for bandwidth efficient real-time transmission of digital media content over IP networks.

The compact, rugged and lightweight IP-900 is ideal for fixed and mobile applications. The low encode-decode latency of less than 400ms makes it well suited for remote news capture and live-event applications.

Utilizing advanced H.264 HP@L4 image processing algorithms, the IP-900 produces exceptional video performance over IP contribution and distribution networks. High performance H.264 compression algorithms reduce the streaming bit rate by about 50% compared to MPEG-2 systems while preserving video fidelity. HD content can now be transported over existing private or public IP network as low as 1 Mbps.

Powerful error correction and retransmission (FEC/ARQ) technology enables the IP-900 to transmit a robust, error free transport stream across private and public IP networks.

IP-900 Specifications		
Video	Input	HD/SD-SDI HDMI CVBS (NTSC/PAL)
	Input Standards	1080i (60/59.94/50 Hz) 720p (59.94/50Hz) 480i (59.94 Hz) 576i (50 Hz)
	Resolution / Bitrate	1920x1080i / 4 – 27 Mbps 1440x1080i / 4 – 27 Mbps 960x1080i / 1 – 27 Mbps 1280x720p / 4 – 27 Mbps 960x720p / 4 – 27 Mbps 640x720p / 1 – 27 Mbps 720x480i / 1 – 10 Mbps 720x576i / 1 – 10 Mbps 352x480i / 0.5 – 10 Mbps 352x576i / 0.5 – 10 Mbps 352x240i / 50 – 512 kbps 352x288i / 50 – 512 kbps 176x122i / 25 – 50 kbps 176x144i / 25 – 50 kbps
	Color Format	4:2:0
	Profile	HD – HP@L4 & MP@L4 SD – HP@L3, MP@L3 & MP@L1.3
	GOP	12 ~ 60 Frames (IBBP) 12 ~ 60 Frames (IPPP) 30 ~ 144 Frames (PPPP)
	Latency modes	Standard IP – 1.3 Sec Low IP – .4 Sec
Audio	Input	1 Pair SDI embedded 1 Pair HDMI 1 Pair Analog Stereo (unbalanced)
	Compression	MPEG1 Layer 2 MPEG2-AAC
	Sample rate	48kHz, 16 bit
Transport Stream	Format	MPEG2 TTS, MPEG-2 TS
	Data rate	~ 30 Mbps with 1 kbps increments
Network Interface	10BASE-T / 100BASE-T	
Forward Error Correction	Fujitsu FEC and ARQ Pro-MPEG FEC CoP3	
Protocols	IPv4 & IPv6 UDP, RTP, Multicast and Unicast	
Monitoring & Control	Web GUI / SNMP	
Size	1RU x 8.3"W x 11.8"D	
Weight	5.1 lb (2.3kg)	
Power Supply	100 – 240 VAC	
Power Consumption	Max 30W	
Operating Temperature	-10 to 55 C	
Certifications	UL, CE, FCC, RoHS	

For more information, call us at **877-766-7545 (toll free in the US)** or visit our website at: [fujitsufrontechna.com](http://fujitsufrontechna.com)

Fujitsu Frontech North America, Inc.

<http://us.fujitsu.com/ffna>

25902 Towne Centre Drive, Foothill Ranch, CA. 92610

©2009 Fujitsu Frontech North America, Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks and The Possibilities are Infinite is a trademark of Fujitsu Ltd. All other trademarks are the property of their respective owners. All statements herein are valid only in the U.S. for U.S. residents, are based on normal operating conditions, are provided for informational purposes only, and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Frontech North America, Inc. reserves the right to modify at any time without prior notice these statements, our products, their performance specifications, availability, price, and warranty and post-warranty programs.

